

## **FUJINON**

Ver 3

		Ver.3.1
型番	<b>Product Name</b>	HF25SA-1
焦点距離 [mm]	Focal length [mm]	25
	(design value)	(23.99)
絞り範囲 (F値)	Iris range (Fnumber)	F1.4-F22
画角 (H×V)	Angle of view	20.8° × 15.7° (2/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 100
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of rocus  Operation of iris	Manual
アイルタ径 [mm]	Filter thread [mm]	M49 × 0.75
マウント	Mount	C-mount
てリンド    質量(約)[g]	Weight (approx.) [g]	315
<u>両</u>	Sensor size (std.)	
適合センサーサイズ(最大)	Sensor size (std.) Sensor size (max.)	2/3" (3.45μm) 2/3" (3.45μm)
10日 ピンリーリイク(取入)  バックフォーカス(空気換算長) [mm]	Back focal length (in air) [mm]	2/3 (3.43µiii) 22.32
		17.53
フランジバック [mm] 入射瞳位置 (マウント面から) [mm]	Flange back [mm]	-42.87
	Entrance pupil position (from Mount) [mm]	
 射出瞳位置(結像面より)[mm]	Exit pupil position	-144.93
	(from image plane) [mm]	
  前側主点 (マウント面から) [mm]		-23.47
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]  Rear principal point (from Mount) [mm]	-23.47
支側主点 (マワンド面がの) [mm]  主点間隔 [mm]		17
	Distance between the principal points [mm]	-0.06
TVディストーション [%]	TV distortion [%]	
外形寸法 [mm]	Dimension [mm]	φ51 × 75.5
主光線入射角度 [°] 周辺光量比 (F4.0·対角端) [%]	Chief Ray Angle [°]	
	Relative illumination [%]	100
	(Aperture: F4.0,	
	Image height: at diagonal)	
周辺光量比 (開放·対角端) [%]	Relative illumination [%]	72
	(Aperture: at full open,	12
使用温度範囲	Image height: at diagonal)	-10°C ∼ +50°C
	Operation Temperature Range	
保存温度範囲	Storage Temperature Range	-20°C ∼ +60°C

These specifications are subject to change without notice.

Entrance pupil position and Exit pupil position are calculated by "chief ray of 60% image height".