

## **FUJINON**

Ver.3

		Ver.3.1
型番	Product Name	HF35SA-1
焦点距離 [mm]	Focal length [mm]	35
馬忌卑離 [mm] 	(design value)	(35.74)
絞り範囲 (F値)	Iris range (Fnumber)	F1.4-F22
画角 (H × V)	Angle of view	14.0° × 10.5° (2/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 200
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	$M49 \times 0.75$
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	185
適合センサーサイズ(標準)	Sensor size (std.)	2/3" (3.45μm)
適合センサーサイズ(最大)	Sensor size (max.)	2/3" (3.45μm)
バックフォーカス(空気換算長)[mm]	Back focal length (in air) [mm]	14.99
フランジバック [mm]	Flange back [mm]	17.53
入射瞳位置(マウント面から)[mm]	Entrance pupil position	-1.66
7	(from Mount) [mm]	
射出瞳位置(結像面より)[mm]	Exit pupil position	-37.12
	(from image plane) [mm]	
前側主点(マウント面から)[mm]	Front principal point (from Mount) [mm]	-1.27
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-18.21
主点間隔 [mm]	Distance between the principal points [mm]	-16.94
TVディストーション [%]	TV distortion [%]	0.07
外形寸法 [mm]	Dimension [mm]	φ51 × 48.5
主光線入射角度 [°]	Chief Ray Angle [°]	8.21
周辺光量比 (F4.0·対角端) [%]	Relative illumination [%]	98
	(Aperture: F4.0,	
	Image height : at diagonal)	
周辺光量比 (開放・対角端) [%]	Relative illumination [%]	
	(Aperture: at full open,	62
	Image height : at diagonal)	1000
使用温度範囲	Operation Temperature Range	$-10^{\circ}\text{C} \sim +50^{\circ}\text{C}$
保存温度範囲	Storage Temperature Range	-20°C ∼ +60°C

These specifications are subject to change without notice.

Entrance pupil position and Exit pupil position are calculated by "chief ray of 60% image height".