

FUJINON

Ver.3

		Ver.3.1	
型番	Product Name	HF75SA-1	
焦点距離 [mm]	Focal length [mm]	75	
焦泉起離 [11111]	(design value)	(74.98)	
絞り範囲 (F値)	Iris range (Fnumber)	F1.8-F22	
画角 (H×V)	Angle of view	6.7° × 5.0° (2/3")	
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 900	
操作方法:フォーカス	Operation of focus	Manual	
操作方法:アイリス	Operation of iris	Manual	
フィルタ径 [mm]	Filter thread [mm]	M49 × 0.75	
マウント	Mount	C-mount	
質量(約)[g]	Weight (approx.) [g]	305	
適合センサーサイズ (標準)	Sensor size (std.)	2/3" (3.45μm)	
適合センサーサイズ(最大)	Sensor size (max.)	2/3" (3.45μm)	
バックフォーカス(空気換算長)[mm]	Back focal length (in air) [mm]	24.43	
フランジバック [mm]	Flange back [mm]	17.53	
入射瞳位置(マウント面から)[mm]	Entrance pupil position (from Mount) [mm]	-1.99	
射出瞳位置(結像面より)[mm]	Exit pupil position (from image plane) [mm]	-52.50	
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-34.56	
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-57.45	
主点間隔 [mm]	Distance between the principal points [mm]	-22.89	
TVディストーション [%]	TV distortion [%]	0.01	
 外形寸法 [mm]	Dimension [mm]	φ51 × 76.0	
主光線入射角度[°]	Chief Ray Angle [°]	5.95	
周辺光量比 (F4.0·対角端) [%]	Relative illumination [%] (Aperture: F4.0, Image height: at diagonal)	99	
周辺光量比 (開放・対角端) [%]	Relative illumination [%] (Aperture: at full open, Image height: at diagonal)	81	
使用温度範囲	Operation Temperature Range	-10°C ∼ +50°C	
保存温度範囲	Storage Temperature Range	$-20^{\circ}\mathrm{C} \sim +60^{\circ}\mathrm{C}$	

These specifications are subject to change without notice.

Entrance pupil position and Exit pupil position are calculated by "chief ray of 60% image height".